



ETR⁺ 1524

Efficient : Trusted : Reliable

PRODUCT DESCRIPTION

The fully Digital Controlled ETR⁺ 1524 rectifier module is designed and optimized for the demanding power needs across different applications and industries.

The modularity design, coupled with its cost-effectiveness package, power density and reliability, ensures the overall availability and performance of the system solution.

KEY FEATURES

- **Fully Digital Controlled**
Reduces component count and improves reliability
- **Modular, Scalable and Hot Swappable**
Flexible installations
- **High Power Density**
Reduces footprint
- **Highly Efficient @ up to 95%**
Reduces losses and lowers operating costs
- **Front-to-back Airflow**
Unobstructed scalability of shelves
- **Excellent EMC Performance**
Lower interference and excellent susceptibility
- **Wide Input Voltage Range**
Continued operation in demanding grid conditions
- **Wide Temperature Range**
Applications in harsh climatic conditions
- **Compliant with Global Standards**
Delivers quality, performance and reliability in power solutions.

APPLICATIONS

- Alarm System
- Control and Monitoring
- Relay Logic (PLC)



TECHNICAL SPECIFICATIONS

PART NUMBER		381090.100
Capacity		1500W
AC INPUT		
Voltage Range		85Vac to 305Vac (Nominal @ 185Vac to 275Vac)
Voltage Range (DC)		100Vdc to 305Vdc (Nominal @ 210Vdc to 275Vdc)
Frequency		45Hz to 66Hz
Maximum Input Current		Max 9Arms @ 185Vac (full load)
Power Factor		≥0.99 @ rated input and ≥50% load
Input Protection		Varistors for transient protection, Mains Fuse for both input lines Shutdown @ > 305Vac with hysteresis
DC OUTPUT		
Output Voltage		27Vdc (adjustable 21Vdc to 29Vdc)
Output Power (Maximum)		1500W @ nominal input
Output Current (Maximum)		62.5A @ 24Vdc with nominal input
Peak Efficiency		up to 95%
Current Sharing		≤±5% of max current from 20% to 100% load
Static Voltage Regulation		≤±0.6% from 10% to 100% load
Dynamic Voltage Regulation		≤±5% for 10%-90% or 90%-10% load variation, regulation time <50ms
Hold Up Time		>20ms; output voltage >22Vdc @ 750W
Ripple and Noise		≤150mVp-p, 20MHz bandwidth ≤2mVrms psophometric
Output Protection		Overvoltage shutdown; hot plug-in, inrush current limiting; high temperature protection; short circuit proof
CONTROL and MONITORING		
Rectifier Alarm and Signaling		High & low mains shutdown, high temperature shutdown, rectifier failure, overvoltage shutdown, fan failure, communication failure
Visual Indications		Alarms - RED
		Warning - YELLOW
		Normal operation - GREEN
OTHER SPECIFICATIONS		
Isolation		Input to Output: 3.0kVac, Input to Earth: 1.5kVac, Output to Earth: 0.5kVdc
Cooling		Fan-cooled, front to back airflow
Fan Speed		Regulated by temperature and output power
MTBF		> 300,000 hrs @ 25°C
ENVIRONMENTAL		
Operating Temperature Range		-40°C to +75°C (de-rates above 55°C)
Storage Temperature Range		-40°C to +85°C
Relative Humidity		Operating: 5% to 90% RH non-condensing
		Storage: 0% to 99% RH non-condensing
Acoustic Noise		≤58dB @ full load, 25°C
PHYSICAL		
Dimensions WxDxH (mm)		109 x 311 x 41 (1U)
Net Weight (kg)		≤1.7
DESIGN STANDARDS		
Electrical Safety		EN/IEC62368-1
EMC		ETSI EN 300 386 V1.6.1
Others		CE, RoHS compliant

Due to continuous product development, specifications are subject to change without prior notice

Rev.1.1